

MODEL TL-5930



International size reference: D, ER32L615

TECHNICAL DATA

(Typical values @+ 25°C for batteries stored for one year or less)



- Nominal capacity @ 4 mA, to 2 V 19 Ah
- Rated voltage 3.6 V
- Maximum recommended continuous current 230 mA
- Maximum pulse current capability 500 mA
- Weight 93 g (3.28 oz)
- Volume 51 cc
- Operating temperature range -55 °C to +85 °C
- Li metal content approx. 5 g
- U.L. Component Recognition, MH 12193
- ✓ IEC 60086-4 certified

TADIRAN LITHIUM BATTERIES



TERMINATIONS & ORDERING NO.

SUFFIX- /S STANDARD	15-5930-21500
SUFFIX- /T SOLDER TABS	15-5930-31500



iXtra - Long Term High Performance

Note: Any presentations in this data sheet concerning performance are for information purpose only and are not construed as warranties either expressed or implied, of future performance.

ECN 1501879 Rev. C 11/08

TL-5930


CELL FEATURES

- 3.6 V Primary lithium-thionyl chloride (Li-SOCl₂)
- Fast voltage recovery after long term storage and/or usage
- High energy density
- Low self discharge rate
- Bobbin construction
- Hermetic glass-to-metal-sealing
- Non-flammable electrolyte
- Restricted for transportation (Class 9 worldwide)
- Non-restricted within the US

TADIRAN LITHIUM BATTERIES

MAIN APPLICATIONS



- Utility meters (elect., water & gas)
- Automatic meter reading
- RF systems
- Sensors & monitoring systems
- Tracking systems
- Wireless security systems
- Automotive electronics
- Industrial electronics
- Ultra Low Power (ULP) devices
- Others



STORAGE CONDITIONS

- Cells should be stored in a clean & dry (less than 30 % RH) area
- Temp. should not exceed +30 °C

For updated information please visit our website www.tadiranbat.com



iXtra - Long Term High Performance

Note: Any presentations in this data sheet concerning performance are for information purpose only and are not construed as warranties either expressed or implied, of future performance.

ECN 1501879 Rev. C 11/08